



## dLAN TV Sat



### Technical specifications

<b>Device port</b>	F-jack (coax) Ethernet RJ45 Hollow plug (OD: 5.5mm/0.217", ID: 2.1mm/0.083")
<b>Standards</b>	Ethernet specifications IEEE 802.3, IEEE 802.3x, IEEE 802.3u, Auto MDI / X HomePlug AV DVB-S, DVB-S2
<b>Range</b>	200 m
<b>Security</b>	128-bit AES encryption over power supply grid (enabled at the touch of a button)
<b>Protocols</b>	CSMA/CA over power supply grid
<b>Transmission speed</b>	200 Mbps
<b>Transmission method</b>	asynchronous
<b>Modulation</b>	OFDM - 1155 carriers, 1024/256/64-QAM, QPSK, BPSK
<b>LEDs</b>	<ul style="list-style-type: none"><li>▪ On</li><li>▪ Connect</li><li>▪ Ethernet (Link/Act)</li><li>▪ Power supply<ul style="list-style-type: none"><li>▪ Power / Power save</li><li>▪ Ethernet (Link / Act)</li><li>▪ dLAN (Link / Act / Quality)</li></ul></li></ul>
<b>Power consumption</b>	30 W
<b>Power supply</b>	12V, 1.5A
<b>Electric power supply</b>	200 – 240 V
<b>Temperature</b>	Storage: -25°C – 70°C Operation: 0°C – 40°C
<b>Weight</b>	762 g (including power supply)
<b>Dimensions</b>	30 x 117 x 191 mm (height x width x depth)
<b>Ambient conditions</b>	10–90% humidity (non-condensing)
<b>System requirements</b>	Ethernet interface Coax cable with F-connector with satellite access USB port for infrared receiver (remote control)
<b>Operating systems</b>	Windows <sup>®</sup> XP <sub>32bit</sub> , Windows <sup>®</sup> Vista <sub>32/64-bit</sub>
<b>Certifications</b>	CE-compliant in accordance with the technical requirements of all EU countries and Switzerland: EN 60950-1:2001 + A11:2004, EN 55024:1998 + A1:2001 + A2:2003, EN 55020:2007, EN 55022:2006 (Class B), EN 55013:2001 + A1:2003 + A2:2006



## dLAN TV Sat



### Sales information

<b>Article number</b>	01197 (DE)
<b>EAN code</b>	4250059611979 (DE)
<b>Warranty</b>	3 years
<b>Service &amp; Support</b>	Phone and e-mail support. Please see the included support flyer or the devolo website for telephone numbers and e-mail addresses.
<b>Design</b>	dLAN TV Sat: Metal/plastic housing dLAN Power supply 200-18: Plastic housing (same form factor as power supply) dLAN 200 AVEasy: Plastic wallplug adapter
<b>Weight</b>	1580 g
<b>Package dimensions</b>	188 x 302 x 115 mm (height x width x depth)
<b>Accessories</b>	Remote control incl. USB infrared receiver (with batteries) Documentation: printed installation guide CD-ROM: <ul style="list-style-type: none"><li>▪ "CyberLink TV Enhance" application software</li><li>▪ PDF manual</li><li>▪ Configuration software for Windows® XP<sub>32-bit</sub>, Windows® Vista<sub>32/64-bit</sub></li><li>▪ Additional software: devolo Informer</li></ul> Coax cable (F-connector) Installation hardware (screws and wallplugs)

### WEEE additional information

<b>Weight WEEE</b>	870 g
<b>Paper (Green Dot)</b>	344 g
<b>Plastic (Green Dot)</b>	20 g
<b>Other (Green Dot)</b>	1 g