



devolo Home Control Central Unit

Technical data

Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 1901 Auto MDI/X ITU-T G.9959 (Z-Wave)
Protocols	CSMA/CA (Powerline) Z-Wave (wireless)
Transmission speeds	Ethernet 10/100 (Mbps) Powerline 200/500 (Mbps)
Modulation • Carrier	Powerline OFDM – (4096)/1024/256/64-QAM, QPSK, BPSK • 2880 Z-Wave: 2-FSK
Range (in m)	Powerline: 300 Z-Wave: 25 (indoors), 100 (outdoors)
Security	128-bit AES (Powerline and Z-Wave)
Buttons	1 x PLC pairing, LED included (white/red) 1 x Home Control, LED included (white/red)
Socket • Countries	Type C (CEE 7/16) • EU
Device port	1 x Ethernet RJ45 1 x USB 2.0 type A (for future extensions)
Power consumption (in W)	Maximum: 4.6 Standard: 4
Temperature (Storage • Operating)	-25 °C to 70 °C • 0 °C to 40 °C
Dimensions (in mm, without plug)	132 x 72 x 42
Ambient conditions	10 – 90 % Humidity (non-condensing)
Operating systems	Windows 7 (32 Bit), Windows 7 (64 Bit) Windows 8 (32-bit), Windows 8 (64-bit), Windows 8 Pro (32-bit), Windows 8 Pro (64-bit) Windows 10 (32 Bit), Windows 10 (64 Bit) Ubuntu Linux 14.04 (32-bit), Ubuntu Linux 14.04 (64-bit) MAC OS X: Mac OS 10.7 or higher Android: 4.0 or higher iOS: iOS 5 or higher
Certifications	CE Class B (EU, CH, NO)
Other	internal speakers (for future extensions)



devolo Home Control Central Unit

Sales information

Warranty	3 years
Accessories	<ul style="list-style-type: none">▪ Printed Install Flyer▪ Ethernet cable

Single adapter

Order number:	09279 (UK)
EAN:	4250059692794
Size:	115 x 190 x 81 mm
Weight:	360 g
WEEE additional information	
Weight WEEE:	200 g
Paper (Green Dot):	100 g
Plastic (Green Dot):	4 g
Other (Green Dot):	0.2 g

© 2017 devolo AG, Germany. All rights reserved.
Technical data subject to change without notice.

Version 03.01.2017